

MagicPin 100T

High quality dot peening system

Our MagicPin 100T system offers affordability and dependability as part of our PinMark line of products. This benchtop marking system has the same great features as our higher end models but at a reduced price.

For those customers who want to get started in the dot peen marking business with a high-quality, low-priced system, this unit provides the same Ostling reliability thousands of customers have experienced. Please contact a sales representative today to find out how this unit can meet your part marking needs.

Features of the MagicPin 100T:

► **Compact, lightweight, flexible**

At under 5kg, it is easy to adapt it to your work flow

► **Fast marking speed gives excellent cycle times**

Marks up to five characters per second for low cycle times

► **Rugged, durable, low-maintenance**


Built to be reliable in industrial environments



UMC eco marking controller

Technical Data MagicPin 100T	
Head dimensions (DxWxH)	188 x 206 x 142mm
Marking field	100 x 100mm
Weight	5kg
Control unit	UMC eco
Maximum part height	300mm (with WE2 needle)
Resolution	0.0635mm per motor step
Needles used	WE2 and WP2
Marking speed	5 characters per second
Compressed air	6 bar (6mm connector)
Power supply	via control unit (110 - 230V AC, 50/60Hz)

Sample markings



Ostling follows a policy of continuous product improvement. Specifications are subject to change without notice.